



System datasheet

FS10-S / FS18-S

General

System	Ballasted PV-mounting system
Components	Ground rails, rail connector, building protection mat, low post, high post, wind deflector, clamps
System warranty	10 years
Application area	Flat roof on industrial, agricultural and residential buildings
Roof covering	Bitumen, concrete, foil, gravel
Roof slope	max. 5° without additional measures

System properties

System orientation	South
Module tilt	10° / 18°
System weight approx.	2.2 kg/m ² (FS10-S) / 2.3 kg/m ² (FS18-S) plus ballast (project specific)
Weight PV-module included approx.:	9.3 kg/m ² (FS10-S) / 8.1 kg/m ² (FS18-S) plus ballast (project specific)
Friction coefficient	$\mu = 0,5$ is to be determined and ensured upon installation surface
Material	Aluminum, stainless steel, strip-galvanized steel metal sheet, rubber granulate
Minimum edge distance	0,6 m
Shading angle	12° to 17,5°

PV-Modules

Type	Suitable for standard 60 cell panels. Approval for panel corner clamping is to be obtained.
Module width	10°: 950-1,050 mm / 18°: 975-1,010 mm
Orientation	Horizontal/Landscape

Certification

Wind loads	Determined in wind tunnel tests by Ruscheweyh Consult GmbH
------------	--

Services

Layout and ballast plan	Provided by Renusol
-------------------------	---------------------

System	Ground rail #	Inter-row spacing approx. [mm]	Shading angle
FS10-S	500400	1,490	17,5°
FS10-S	500401	1,740	12,0°
FS18-S	500402	1,840	17,5°
FS18-S	500403	2,090	14,5°